

Environmental Protection Agency

§ 421.132

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/troy ounce of silver production	
Copper000	.000
Zinc000	.000
Ammonia (as N)000	.000

[49 FR 8821, Mar. 8, 1984; 49 FR 26739, June 29, 1984]

§ 421.127 [Reserved]

Subpart M—Secondary Lead Subcategory

SOURCE: 49 FR 8826, Mar. 8, 1984, unless otherwise noted.

§ 421.130 Applicability: Description of the secondary lead subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of lead by secondary lead facilities.

§ 421.131 Specialized definitions.

For the purpose of this subpart the general definitions, abbreviations, and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

§ 421.132 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable technology currently available:

(a) Subpart M—Battery Cracking

BPT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead scrap produced	
Antimony	1.932	.862
Arsenic	1.407	.579

BPT EFFLUENT LIMITATIONS—Continued

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
Lead283	.135
Zinc983	.411
Ammonia (as N)000	.000
Total suspended solids	27.600	13.130
pH	(¹)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

(b) Subpart M—Blast, Reverberatory, or Rotary Furnace Wet Air Pollution Control

BPT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead produced from smelting	
Antimony	7.491	3.341
Arsenic	5.455	2.245
Lead	1.096	.522
Zinc	3.811	1.592
Ammonia (as N)000	.000
Total suspended solids	107.000	50.900
pH	(¹)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

(c) Subpart M—Kettle Wet Air Pollution Control

BPT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead produced from refining	
Antimony129	.058
Arsenic094	.039
Lead019	.009
Zinc066	.027
Ammonia (as N)000	.000
Total suspended solids	1.845	.878
pH	(¹)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

(d) Subpart M—Lead Paste Desulfurization

BPT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead processed through desulfurization	
Antimony000	.000
Arsenic000	.000